



*The Ultimate Dirt Race Cars*

83 S. Broadview St Greenbrier, AR 72058 • Phone: 501.679.2311 • www.TeamGRT.com

## 2010 LATE MODEL **SIGNATURE SERIES** SETUP SHEET

### RIDE HEIGHTS:

LF: 2 7/8"  
RF: 2 7/8"  
RR: 12 1/2"  
LR: Set with bite

### FRONT END ALIGNMENT:

<u>CASTER:</u>	<u>CAMBER:</u>
LF: 1.5+	LF: 4+
RF: 3.0+	RF: 4 -

### UPPER A-ARM LENGTHS:

<u>LOWER:</u>	<u>UPPER:</u>
LF: 17 5/8"	LF: 12 1/4"
RF: 19 1/8"	RF: 8 1/2"

### TIE ROD LENGTHS:

LF: 17 1/2"  
RF: Set with toe

### BUMP STEER SETTINGS:

LF: Tie rods go down 7/10<sup>th</sup> degree more than lower a-arm  
RF: Tie rods go down 4/10<sup>th</sup> degree more than lower a-arm

### UPPER A-FRAME LOCATION:

LF: 4 5/8" from top of frame to center location of shaft  
RF: 5 5/8" from top of frame to center location of shaft

### PANHARD BAR FRAME MOUNT:

8 3/8" from bottom of frame to bottom of bracket (flat part in front)

\*Start 4<sup>th</sup> notch up on frame

\*Start 2<sup>nd</sup> notch up on pinion

**Panhard bar length 21 1/4" center to center**

### 4 BARS:

TOP: 17" center to center  
BOTTOM: 15" center to center

### TORQUE ARM :

Start 4<sup>th</sup> hole from back

### STANDARD SPRINGS

LF: 550 x 10      RF: 350 x 10  
LR: 225 x 14      RR: 225 x 12  
Torque Arm: 325 x 10